# TensionLite Plus 10 ft. Wave Shape Mural Wall Design 5

TensionLite is a collection of sophisticated, ergonomically designed exhibit booths. Formulate combines state-of-the-art zipper pillowcase dye-sublimated fabric coverings with advanced lightweight aluminum structures to provide unique design, functionality, and style. The excellence of the Formulate line of displays, hanging structures and products is simply unmatched. Stretch fabric graphics are hand-sewn, durable and dry-cleanable.




## features and benefits:

- State-of-the-art 30mm aluminum tube frame with snap button assembly
- Four laminate color options available
- Countertop holds max 10 lbs / 4.5 kgs
- Design includes: one frame, one dye-sublimated zipper pillowcase graphic, table, stand-off literature pockets, and one wheeled molded OCL and OCH2 storage case
- Lifetime hardware warranty against manufacturer defects

## dimensions:

| Hardware | Graphic |
|---|---|
| Assembled unit:<br>117.7”w x 96.2”h x 37.7”d<br><br>Counter dimensions:<br>20.5”w x 1.2”h x 11.8”d<br>Stand-off literature rack:<br>23.6”w x 92.7”h x 19.15”d<br><br>Approximate weight (includes graphics):<br>49.63 lbs / 22.5 kgs | Refer to related graphic templates for more information. |
| Shipping | |
| Shipping dimensions - ships in two cases:<br>One OCL case: 56”l x 19”h x 19”d<br>One OCH2 case: 52”l x 29”h x 15”d<br><br>Approximate shipping weight (with cases):<br>110 lbs / 50 kgs | |

## additional information:


Graphic materials:
Dye-sublimated zipper pillowcase fabric,
3mm white PVC

Table colors:


silver black mahogany natural


We are continually improving and modifying our product range and reserve the right to vary the specifications without prior notice. All dimensions and weights quoted are approximate and we accept no responsibility for variance. E&OE. See Graphic Templates for graphic bleed specifications.


| Parts Included | | |
|---|---|---|
| **Part Label** | **Qty** | **Part Code** |
| FABRIC GRAPHIC | x1 | WV10-01-G |
| LN114 BOLT | x2 | LN114 BOLT |
| 90 DEGREE ELBOW JOINT FOR 30MM TUBING | x2 | TC-30-90 |
| 1270MM X 30MM TUBE | x6 | WV10-01-T1 |
| 30MM CURVED TUBE WITH PART T AND 90B LEFT SIDE | x1 | WV10-01-T2-L |
| 30MM CURVED TUBE WITH PART T AND 90B RIGHT SIDE | x1 | WV10-01-T2-R |
| R2250 (1163MM ARC) CURVED TUBE | x4 | WV10-01-T2 |
| (2) 128MM TUBES SWAGED WITH PART TC-30-T | x1 | WV10-01-T4 |
| (2) 128MM TUBES SWAGED WITH PART TC-30-T | x1 | WV10-01-T7 |
| (2) 128MM TUBES SWAGED WITH PART TC-30-X | x1 | WV10-01-T5 |
| STEEL PLATE FOR WVC | x2 | WVC-PLATE-STD |




| Parts Included | | |
|---|---|---|
| **Part Label** | **Qty** | **Part Code** |
| CABLES WITH (3) LITERATURE POCKETS | x1 | CK3 |
| PARALLEL TUBE CLAMP FOR 30MM TUBES | x2 | TCP-3030 |
| 30MM TUBE SECTION | x2 | WL-T3 |
| TOP SINTRA GRAPHICS | x2 | WLLH-T-G |
| 30MM TUBE SECTION | x1 | WL-T2 |
| 30MM TUBE SECTION | x1 | WL-T1 |











| Parts Included | | |
|---|---|---|
| **Part Label** | **Qty** | **Part Code** |
| 8/32 THUMB SCREW | x2 | 8_32_TSCR |
| 520 X 300 X 30 COUNTER | x1 | CTW_L03 |
| SILVER ANODIZE FINISH 30MM TUBE CLAMP | x2 | TC-30 |
| MOUNTED TABLE TOP WITH SUPPORT BRACKET LEFT OR RIGHT SIDE | x1 | WC-L OR WC-R |



## STEP 1: ASSEMBLE FRAME



Assemble top frame corners using TC-30-90. Label codes will be on backside of tube. It is best to assemble frame laying flat.




Connect sides of frame by lining up holes with snap buttons.





Use TC-30-90B to connect bottom frame corners; snap on button.




Frame assembly is complete once all sides and middle are connected.

## STEP 2: ATTACH FEET




Attach feet with Allen key. See next step for detailed view.





Using provided allen key, secure both feet (WVM-BP) to bottom of frame by tightening bolt.


## STEP 3: ATTACH GRAPHIC



Slide graphic over top of frame.





Zip fabric closed as shown along bottom.




Stand unit upright.

## STEP 4: ATTACH COUNTER TO HARDWARE




Install counter to mounting tube with 8/32" thumb screws, repeat for second screw.

## STEP 5: ATTACH COUNTER TO BACKWALL





Secure tube clamp TC-30 around backwall at desired height and tighten with 3/16" hex key tool.





Secure second tube clamp TC-30 around backwall and tighten with 3/16" hex key tool.

## STEP 6: ASSEMBLE STAND-OFF LADDER FRAME




Connect top of accent frame to bottom using WL-T3 by pressing snap buttons.

## STEP 7: ATTACH LITERATURE HOLDER




Twist on cables to top and bottom tubes.





Install brochure holders on cables with CKPS4 using 2mm hex key.

## STEP 8: ATTACH GRAPHICS




Slide infill panels into channels.

## STEP 9: ATTACH TO BACKWALL WITH CLAMPS




Position accent in front of backwall in desired location.




Using provided 5mm hex key, rotate bolt clockwise to secure accent to top of fabric backwall.